

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Petrol DAB 40/60°C (Petroleum ether), 250 ml**

Print date: 14.04.2015

Product code: 9991127

Page 1 of 8

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Petrol DAB 40/60°C (Petroleum ether), 250 ml

CAS No: 101316-46-5

EC No: 309-852-0

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Laboratory chemicals

**1.3. Details of the supplier of the safety data sheet****Seller**

Company name: CONATEX-DIDACTIC Lehrmittel GmbH

Street: Im Forstgarten 1

Place: D-66459 Kirkel

Internet: www.conatex.com

**Supplier**

Company name: Carbolution Chemicals GmbH

Street: Im Stadtwald, Gebäude A1.2

Place: D-66123 Saarbrücken

Contact person: Dr. Michael Bauer Telephone: +49 (0)681 302-71232

e-mail: michael.bauer@carbolution-chemicals.de

Internet: www.carbolution-chemicals.de

**1.4. Emergency telephone number:** +49 (0)681 302-71232**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification according to Directive 67/548/EEC or 1999/45/EC**

Indications of danger: F - Highly flammable, R3 - Repr. Cat. 3, Xn - Harmful, Xi - Irritant, N - Dangerous for the environment

R phrases:

Possible risk of impaired fertility.

Highly flammable.

Irritating to skin.

Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Toxic to aquatic organisms.

May cause long-term adverse effects in the aquatic environment.

Harmful: may cause lung damage if swallowed.

Vapours may cause drowsiness and dizziness.

**Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard categories:

Flammable liquid: Flam. Liq. 2

Reproductive toxicity: Repr. 2

Skin corrosion/irritation: Skin Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Specific target organ toxicity - repeated exposure: STOT RE 2

Aspiration hazard: Asp. Tox. 1

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Petrol DAB 40/60°C (Petroleum ether), 250 ml

Print date: 14.04.2015

Product code: 9991127

Page 2 of 8

Highly flammable liquid and vapour.  
Causes skin irritation.  
May cause damage to organs through prolonged or repeated exposure.  
Suspected of damaging fertility.  
May be fatal if swallowed and enters airways.  
May cause drowsiness or dizziness.  
Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

##### Hazardous components which must be listed on the label

Petrol DAB 40/60°C (Petroleum ether)

Signal word:

Danger

Pictograms:

GHS02-GHS07-GHS08-GHS09



##### Hazard statements

H225 Highly flammable liquid and vapour.  
H315 Causes skin irritation.  
H336 May cause drowsiness or dizziness.  
H361f Suspected of damaging fertility.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H411 Toxic to aquatic life with long lasting effects.

##### Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P240 Ground/bond container and receiving equipment.  
P243 Take precautionary measures against static discharge.  
P260 Do not breathe dust/fume/gas/mist/vapours/spray.  
P271 Use only outdoors or in a well-ventilated area.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P501 Dispose of contents/container to Waste management.

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

#### Hazardous components

EC No	Chemical name	Quantity
CAS No	Classification according to Directive 67/548/EEC	
Index No	Classification according to Regulation (EC) No. 1272/2008 [CLP]	
309-852-0	Petrol DAB 40/60°C (Petroleum ether)	100 %
101316-46-5	Repr. Cat. 3, F - Highly flammable, Xn - Harmful, Xi - Irritant, N - Dangerous for the environment R62-11-38-48/20-51-53-65-67	
	Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 2; H225 H361f H315 H336 H373 H304 H411	

Full text of R-, H- and EUH-phrases: see section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Petrol DAB 40/60°C (Petroleum ether), 250 ml**

Print date: 14.04.2015

Product code: 9991127

Page 3 of 8

**General information**

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

**After inhalation**

Provide fresh air. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

**After contact with skin**

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention.

**After contact with eyes**

Rinse immediately carefully and thoroughly with eye-bath or water. In case of troubles or persistent symptoms, consult an ophthalmologist.

**After ingestion**

Rinse mouth immediately and drink plenty of water.

**4.3. Indication of any immediate medical attention and special treatment needed**

No data available

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

Carbon dioxide (CO<sub>2</sub>). Foam. Extinguishing powder.

**Unsuitable extinguishing media**

Water. Foam.

**5.2. Special hazards arising from the substance or mixture**

Combustible. Vapours may form explosive mixtures with air.

**5.3. Advice for firefighters**

Wear a self-contained breathing apparatus and chemical protective clothing. Full protective suit.

**Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Wear personal protection equipment.

**6.2. Environmental precautions**

Do not allow uncontrolled discharge of product into the environment. Explosion hazard.

**6.3. Methods and material for containment and cleaning up**

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

**Advice on protection against fire and explosion**

Keep away from sources of ignition. - No smoking. Take precautionary measures against static

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Petrol DAB 40/60°C (Petroleum ether), 250 ml

Print date: 14.04.2015

Product code: 9991127

Page 4 of 8

discharges. Vapours may form explosive mixtures with air.

#### **7.2. Conditions for safe storage, including any incompatibilities**

##### **Requirements for storage rooms and vessels**

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from sources of ignition.

- No smoking.

##### **Advice on storage compatibility**

Do not store together with: Material, rich in oxygen, oxidizing.

### SECTION 8: Exposure controls/personal protection

#### **8.1. Control parameters**

#### **8.2. Exposure controls**

##### **Appropriate engineering controls**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

##### **Protective and hygiene measures**

Remove contaminated, saturated clothing immediately. Protect skin by using skin protective cream.

After work, wash hands and face. When using do not eat or drink.

##### **Eye/face protection**

Eye protection: Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): DIN EN 166

##### **Hand protection**

Hand protection: Single-use gloves. Before using check leak tightness / impermeability. Use gloves only once. German Industry Norms (DIN) / European Norms (EN): DIN EN 374

##### **Skin protection**

Body protection: Lab apron. Only wear fitting, comfortable and clean protective clothing.

##### **Respiratory protection**

With correct and proper use, and under normal conditions, breathing protection is not required. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Suitable respiratory protective equipment: particulates filter device (DIN EN 143).

### SECTION 9: Physical and chemical properties

#### **9.1. Information on basic physical and chemical properties**

Physical state:	liquid
Colour:	colourless clear
Odour:	No data available

#### **Test method**

pH-Value:	No data available
-----------	-------------------

##### **Changes in the physical state**

Initial boiling point and boiling range:	50 °C
--	-------

Sublimation point:	No data available
--------------------	-------------------

Softening point:	No data available
------------------	-------------------

Flash point:	-40 °C
--------------	--------

##### **Flammability**

Solid:	No data available
--------	-------------------

Gas:	No data available
------	-------------------

Lower explosion limits:	No data available
-------------------------	-------------------

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Petrol DAB 40/60°C (Petroleum ether), 250 ml

Print date: 14.04.2015

Product code: 9991127

Page 5 of 8

Upper explosion limits:	No data available
Ignition temperature:	No data available
<b>Auto-ignition temperature</b>	
Solid:	No data available
Gas:	No data available
Vapour pressure:	No data available
Vapour pressure:	No data available
Density:	No data available
Water solubility:	No data available
Partition coefficient:	No data available
Viscosity / dynamic:	No data available
Viscosity / kinematic:	No data available
Flow time:	No data available
Vapour density:	No data available
Evaporation rate:	No data available
Solvent separation test:	No data available
Solvent content:	No data available

#### **9.2. Other information**

Solid content:	No data available
----------------	-------------------

### **SECTION 10: Stability and reactivity**

#### **10.1. Reactivity**

No data available

#### **10.3. Possibility of hazardous reactions**

No data available

#### **10.4. Conditions to avoid**

Keep away from heat. Ignition hazard.

#### **10.5. Incompatible materials**

Oxidizing agents, strong.

#### **10.6. Hazardous decomposition products**

In case of fire may be liberated: Carbon monoxide. Carbon dioxide.

### **SECTION 11: Toxicological information**

#### **11.1. Information on toxicological effects**

##### **Toxicokinetics, metabolism and distribution**

Toxicological data are not available.

##### **Acute toxicity**

Toxicological data are not available.

##### **Irritation and corrosivity**

Vapours may cause drowsiness and dizziness. After skin contact: Irritant.

##### **Sensitising effects**

No data available

##### **Severe effects after repeated or prolonged exposure**

No data available

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Petrol DAB 40/60°C (Petroleum ether), 250 ml**

Print date: 14.04.2015

Product code: 9991127

Page 6 of 8

**Carcinogenic/mutagenic/toxic effects for reproduction**

May impair fertility.

**Specific effects in experiment on an animal**

No data available

**Additional information on tests**

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

**Practical experience****Observations relevant to classification**

No data available

**SECTION 12: Ecological information****12.1. Toxicity**

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**12.2. Persistence and degradability**

No data available

**12.3. Bioaccumulative potential**

No data available

**12.4. Mobility in soil**

No data available

**12.5. Results of PBT and vPvB assessment**

No data available

**12.6. Other adverse effects**

No data available

**Further information**

Do not allow to enter into surface water or drains. The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Advice on disposal**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

**Waste disposal number of waste from residues/unused products**

160506 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; laboratory chemicals, consisting of or containing dangerous substances, including mixtures of laboratory chemicals  
Classified as hazardous waste.

**Waste disposal number of used product**

160506 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; laboratory chemicals, consisting of or containing dangerous substances, including mixtures of laboratory chemicals  
Classified as hazardous waste.

**Waste disposal number of contaminated packaging**

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by dangerous substances  
Classified as hazardous waste.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Petrol DAB 40/60°C (Petroleum ether), 250 ml**

Print date: 14.04.2015

Product code: 9991127

Page 7 of 8

**Contaminated packaging**

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

**SECTION 14: Transport information****Land transport (ADR/RID)**

<b>14.1. UN number:</b>	UN 1268
<b>14.2. UN proper shipping name:</b>	PETROLEUM DISTILLATES, N.O.S.
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3
Classification code:	F1
Special Provisions:	363 640C
Limited quantity:	1 L
Transport category:	2
Hazard No:	33
Tunnel restriction code:	D/E

**Other applicable information (land transport)**

E2

**Inland waterways transport (ADN)**

<b>14.1. UN number:</b>	UN 1268
<b>14.2. UN proper shipping name:</b>	PETROLEUM DISTILLATES, N.O.S.
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3
Classification code:	F1
Special Provisions:	363 640C
Limited quantity:	1 L

**Other applicable information (inland waterways transport)**

E2

**Marine transport (IMDG)**

<b>14.1. UN number:</b>	UN 1268
<b>14.2. UN proper shipping name:</b>	PETROLEUM DISTILLATES, N.O.S.
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3
Special Provisions:	363
Limited quantity:	1 L
EmS:	F-E, S-E

**Other applicable information (marine transport)**

E2

**Air transport (ICAO)**

<b>14.1. UN number:</b>	UN 1268
<b>14.2. UN proper shipping name:</b>	PETROLEUM DISTILLATES, N.O.S.
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Petrol DAB 40/60°C (Petroleum ether), 250 ml

Print date: 14.04.2015

Product code: 9991127

Page 8 of 8

Hazard label:	3	
Special Provisions:	A3	
Limited quantity Passenger:	1 L	
IATA-packing instructions - Passenger:		353
IATA-max. quantity - Passenger:		5 L
IATA-packing instructions - Cargo:		364
IATA-max. quantity - Cargo:		60 L

#### Other applicable information (air transport)

E2  
: Y341

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulatory information

##### Additional information

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

##### National regulatory information

Water contaminating class (D): 3 - highly water contaminating

### SECTION 16: Other information

#### Relevant R-phrases (Number and full text)

11	Highly flammable.
38	Irritating to skin.
48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation.
51	Toxic to aquatic organisms.
53	May cause long-term adverse effects in the aquatic environment.
62	Possible risk of impaired fertility.
65	Harmful: may cause lung damage if swallowed.
67	Vapours may cause drowsiness and dizziness.

#### Relevant H- and EUH-phrases (Number and full text)

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361f	Suspected of damaging fertility.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.