

according to Regulation (EC) No 1907/2006

## 2-Butanol (2-Butyl alcohol), 1 I

Print date: 14.04.2015 Product code: 9991178 Page 1 of 8

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

2-Butanol (2-Butyl alcohol), 1 l

CAS No: 78-92-2
Index No: 603-127-00-5
EC No: 201-158-5

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Laboratory chemicals

#### 1.3. Details of the supplier of the safety data sheet

Seller

Company name: CONATEX-DIDACTIC Lehrmittel GmbH

Street: Im Forstgarten 1
Place: D-66459 Kirkel
Internet: www.conatex.com

Supplier

Company name: Carbolution Chemicals GmbH Street: Im Stadtwald, Gebäude A1.2

Place: D-66123 Saarbrücken

Contact person: Dr. Michael Bauer Telephone: +49 (0)681 302-71232

e-mail: michael.bauer@carbolution-chemicals.de

Internet: www.carbolution-chemicals.de

**1.4. Emergency telephone** +49 (0)681 302-71232

number:

#### **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

## Classification according to Directive 67/548/EEC or 1999/45/EC

Indications of danger: Xi - Irritant

R phrases: Flammable.

Irritating to eyes and respiratory system. Vapours may cause drowsiness and dizziness.

# Classification according to Regulation (EC) No. 1272/2008 [CLP]

Hazard categories:

Flammable liquid: Flam. Liq. 3

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3 Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Flammable liquid and vapour.
Causes serious eye irritation.
May cause respiratory irritation.
May cause drowsiness or dizziness.

## 2.2. Label elements

#### Hazardous components which must be listed on the label

butan-2-ol



according to Regulation (EC) No 1907/2006

## 2-Butanol (2-Butyl alcohol), 1 I

Print date: 14.04.2015 Product code: 9991178 Page 2 of 8

Signal word: Warning

Pictograms: GHS02-GHS07





#### **Hazard statements**

H226 Flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.

#### **Precautionary statements**

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

#### **SECTION 3: Composition/information on ingredients**

#### 3.1. Substances

Sum formula: C4H10O Molecular weight: 74,12

## **Hazardous components**

EC No	Chemical name	Quantity
CAS No	Classification according to Directive 67/548/EEC	
Index No	Classification according to Regulation (EC) No. 1272/2008 [CLP]	
201-158-5	butan-2-ol	100 %
78-92-2	Xi - Irritant R10-36/37-67	
603-127-00-5	Flam. Liq. 3, Eye Irrit. 2, STOT SE 3, STOT SE 3; H226 H319 H335 H336	

Full text of R-, H- and EUH-phrases: see section 16.

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### **General information**

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

#### After inhalation

Provide fresh air. Medical treatment necessary.

## After contact with skin

Wash with plenty of water. Change contaminated clothing.

## After contact with eyes

If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 5 minutes. Subsequently consult an ophthalmologist.

#### After ingestion

Rinse mouth immediately and drink plenty of water.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No data available

## **SECTION 5: Firefighting measures**



according to Regulation (EC) No 1907/2006

## 2-Butanol (2-Butyl alcohol), 1 I

Print date: 14.04.2015 Product code: 9991178 Page 3 of 8

#### 5.1. Extinguishing media

## Suitable extinguishing media

Carbon dioxide (CO2). Foam. Extinguishing powder.

#### 5.2. Special hazards arising from the substance or mixture

Combustible. Vapours may form explosive mixtures with air.

#### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

## **Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Wear personal protection equipment.

#### 6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Explosion hazard.

#### 6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

## **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

#### Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

## Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharges. Vapours may form explosive mixtures with air.

#### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from sources of ignition.

- No smoking.

## Advice on storage compatibility

Do not store together with: Material, rich in oxygen, oxidizing.

## **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

### **Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
78-92-2	Butan-2-ol	100	308		TWA (8 h)	WEL
		150	462		STEL (15 min)	WEL

## 8.2. Exposure controls

#### Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe



according to Regulation (EC) No 1907/2006

## 2-Butanol (2-Butyl alcohol), 1 I

Print date: 14.04.2015 Product code: 9991178 Page 4 of 8

gas/fumes/vapour/spray.

## Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Protect skin by using skin protective cream. After work, wash hands and face. When using do not eat or drink.

#### Eye/face protection

Eye protection: Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): DIN EN 166

## Hand protection

Hand protection: Single-use gloves. Before using check leak tightness / impermeability. Use gloves only once. German Industry Norms (DIN) / European Norms (EN): DIN EN 374

## Skin protection

Body protection: Lab apron. Only wear fitting, comfortable and clean protective clothing.

## **Respiratory protection**

With correct and proper use, and under normal conditions, breathing protection is not required. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Suitable respiratory protective equipment: particulates filter device (DIN EN 143).

## **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state: liquid
Colour: colourless

Odour: No data available

Test method

pH-Value: No data available

Changes in the physical state

Melting point:

Initial boiling point and boiling range:

Sublimation point:

No data available

Softening point:

No data available

Flash point:

27 °C

**Flammability** 

Solid: No data available Gas: No data available

Lower explosion limits: 1,7 vol. %

Upper explosion limits: 9,8 vol. %

Ignition temperature: No data available

**Auto-ignition temperature** 

Solid: No data available
Gas: No data available
Vapour pressure: 15.3 hPa

(at 20 °C)

Vapour pressure: 24,4 hPa

(at 25 °C)

Density: No data available Water solubility: No data available Partition coefficient: 0,146



according to Regulation (EC) No 1907/2006

2-Butanol (2-Butyl alcohol	I), 1	ı
----------------------------	-------	---

Print date: 14.04.2015 Product code: 9991178 Page 5 of 8

Viscosity / dynamic:

Viscosity / kinematic:

No data available

No data available

No data available

Vapour density:

2,56

Evaporation rate:

No data available

No data available

Solvent separation test:

No data available

No data available

No data available

9.2. Other information

Solid content: No data available

## **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

No data available

#### 10.3. Possibility of hazardous reactions

No data available

## 10.4. Conditions to avoid

Keep away from heat. Ignition hazard.

#### 10.5. Incompatible materials

Oxidizing agents, strong.

## 10.6. Hazardous decomposition products

No data available

## **SECTION 11: Toxicological information**

## 11.1. Information on toxicological effects

## Toxicocinetics, metabolism and distribution

Toxicological data are not available.

## **Acute toxicity**

CAS No	Chemical name				
	Exposure routes	Method	Dose	Species	Source
78-92-2	butan-2-ol				
	oral	LD50	2190 mg/kg	Ratte	

#### Irritation and corrosivity

Irritating to eyes. Following inhalation: Lung irritation. Coughing. shortage of breath.

## Sensitising effects

No data available

### Severe effects after repeated or prolonged exposure

No data available

## Carcinogenic/mutagenic/toxic effects for reproduction

Due to missing data no statement can be made whether the substance fullfills the criteria of CMR categories 1 or 2. Practical experiences do not give any evidence for CMR activity of categories 1 or 2.

## Specific effects in experiment on an animal

No data available



according to Regulation (EC) No 1907/2006

## 2-Butanol (2-Butyl alcohol), 1 I

Print date: 14.04.2015 Product code: 9991178 Page 6 of 8

#### Additional information on tests

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

#### Practical experience

#### Observations relevant to classification

No data available

## **SECTION 12: Ecological information**

#### 12.1. Toxicity

CAS No	Chemical name					
	Aquatic toxicity	Method	Dose	[h]   [d]	Species	Source
78-92-2	butan-2-ol					
	Acute fish toxicity	LC50	3670 mg/l	96 h	Pimephales promelas	

#### 12.2. Persistence and degradability

No data available

## 12.3. Bioaccumulative potential

No data available

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
78-92-2	butan-2-ol	0,65

#### 12.4. Mobility in soil

No data available

#### 12.5. Results of PBT and vPvB assessment

No data available

## 12.6. Other adverse effects

No data available

#### **Further information**

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

## **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

## Advice on disposal

Dispose of waste according to applicable legislation.

## Waste disposal number of waste from residues/unused products

160506 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded

chemicals; laboratory chemicals, consisting of or containing dangerous substances, including mixtures

of laboratory chemicals

Classified as hazardous waste.

#### Waste disposal number of used product

160506 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded

chemicals; laboratory chemicals, consisting of or containing dangerous substances, including mixtures

of laboratory chemicals

Classified as hazardous waste.

#### Waste disposal number of contaminated packaging



according to Regulation (EC) No 1907/2006

## 2-Butanol (2-Butyl alcohol), 1 I

Print date: 14.04.2015 Product code: 9991178 Page 7 of 8

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE

CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by dangerous substances

Classified as hazardous waste.

#### Contaminated packaging

Water (with cleaning agent). Completely emptied packages can be recycled.

UN1120

30

D/E

#### **SECTION 14: Transport information**

# Land transport (ADR/RID) 14.1. UN number:

Hazard No:

14.2. UN proper shipping name:	BUTANOLS
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3
Classification code:	F1
Limited quantity:	5 L
Transport category:	3

# Other applicable information (land transport)

F1

Tunnel restriction code:

#### Inland waterways transport (ADN)

14.1. UN number:	UN1120
14.2. UN proper shipping name:	BUTANOLS

14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3Classification code:F1Limited quantity:5 L

## Other applicable information (inland waterways transport)

E1

## Marine transport (IMDG)

14.1. UN number:	UN1120
14.2. UN proper shipping name:	BUTANOLS

14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3Special Provisions:223Limited quantity:5 LEmS:F-E, S-D

## Other applicable information (marine transport)

E1

## Air transport (ICAO)

14.1. UN number:UN112014.2. UN proper shipping name:BUTANOLS

14.3. Transport hazard class(es):



according to Regulation (EC) No 1907/2006

2-Butanol (2-Butyl alcohol), 1	2-Butanol	(2-Buty	l alcohol)	. 1 I
--------------------------------	-----------	---------	------------	-------

Print date: 14.04.2015 Product code: 9991178 Page 8 of 8

14.4. Packing group:IIIHazard label:3Special Provisions:A3Limited quantity Passenger:10 L

IATA-packing instructions - Passenger: 355
IATA-max. quantity - Passenger: 60 L
IATA-packing instructions - Cargo: 366
IATA-max. quantity - Cargo: 220 L

Other applicable information (air transport)

E1 ∶ Y344

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

## **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**EU** regulatory information

2004/42/EC (VOC): 100 %

**Additional information** 

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

National regulatory information

Water contaminating class (D): 1 - slightly water contaminating

## **SECTION 16: Other information**

#### Relevant R-phrases (Number and full text)

Flammable.

36/37 Irritating to eyes and respiratory system.Vapours may cause drowsiness and dizziness.

# Relevant H- and EUH-phrases (Number and full text)

H226 Flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.